

Premocoat™

Premocoat™ is a line of Portland cement based materials and complementary materials for finishing horizontal and vertical surfaces. Products include Premocoat™ Base, EIFS Finish, SBC, Microrender, Bonder, Sealer and Color Pack.

Premocoat™ Base

Polymer modified cement based powder applied in thin coats. Available in 50 lb bags with a gray or white cement base. Standard (see Premocoat™ Color Chart) or custom Color Packs can be mixed in to add color. Applied by trowel, roller or sprayer. Compressive strength: 4,500 psi. Applications:

- Thin finish stucco: Two 1/16" thick coatings applied
- Surface leveler for horizontal and vertical surfaces
- EIFS base coat: Applied over expanded polystyrene (EPS) used in EIFS. Mesh then embedded in base coat
- Priming surface for stampable overlays: Applied over horizontal and vertical surfaces as primer prior to application of Premocoat™ SBC as a stampable overlay
- Repair and resurfacing of existing concrete



Premocoat™ EIFS Finish

Self curing, polymer modified, cement based fine aggregate powder. Available in gray, white or specified color in 50 lb bags. Mold/mildew and freeze/thaw resistant. Applications:

- Smooth finish coat for Exterior Insulated Finishing Systems (EIFS)
- Smooth topping over a Premocoat™ Base coat resurfacing of existing concrete: Due to fine particle distribution it will featheredge without crumbling and can be used on interior and exterior surfaces

Premocoat™ SBC

Polymer modified, fiber reinforced, single component powder. Available in 50 lb bags in a gray or white base and accepts integral color. Compressive strength: 4,400 psi. Flexural strength: 1,500 psi. Applications:

- Surface bonding cement and stucco
- Stampable overlay: Can be used with vertical and horizontal surfaces and interior and exterior walls. Accepts color hardeners, integral color and sealers

Premocoat™ Microrender

Portland based, polymer modified coating. Economical stain or paint alternative that can be sprayed, brushed or rolled. In gray, white or colored to specification and available in 5 gallon pails. Mixed with water only prior to use. Applications:

- Single coat provides a semi-transparent stain-like appearance. Two coats provide an opaque paint-like appearance. When applied to uncured concrete will cure with the substrate creating a stronger bond. No primer needed prior to use.



Premocoat™ Bonder

Liquid concentrated acrylic polymer emulsion used as a primer and available in 5 gallon pails. Applications:

- Promote adhesion between cementitious substrate and new Portland cement based coating
- Admixture for Premocoat™ SBC: Enhances moisture, chemical and UV resistance.

Premocoat™ Sealer

Clear acrylic sealer containing 25% solids. Available in 5 gallon pails. Applications:

- Provides additional moisture resistance for concrete and cementitious finishes
- Makes colored finishes more vibrant and glossier
- Creates an easier to clean, more mold and mildew resistant surface



Premocoat™ Color Pack

Dry powder pigments in small packs. Standard colors viewed on Premocoat Color Chart. Can be added to and mixed with Premocoat™ Base, EIFS Finish, SBC and Microrender

Cresco Concrete Products, LLC

1905 Johanna Drive, Suite B2
Houston, TX 77055
info@CrescoConcrete.com
www.CrescoConcrete.com



Phone 713.589.5043
Toll Free 866.491.6819
Fax 713.589.9025
Technical Service 832.533.2527